

Replace your Propane & CO alarms that are over 5 years old!

Mini Dual CO/ Propane Alarm



SAFE-T-ALERT™ RV Carbon Monoxide / Propane Gas Alarm

Green - On Red - Alarm Red/Green - Fault

Red Red / Green Gree

25-741 12vDC 108

Replace By: 60 Mo

■ LP Do Not Paint SAFE-T-ALERT™ RV Carbon Monoxide / Propane Gas Alarm Green - On LP Red - Alarm Do Not Paint Red/Green Fault Red Red / Green Green - End of Life

CO
During Alarm; Move to Fresh Air, Call 911

TEST WEEKLY _____ 25-741 12vDC 108mA

Replace By: 60 Months After Retail Sale / Est 60 Mois

25-741 Surface Mount Models: 25-741-WT (White) 25-741-BL (Black)

25-742 Flush Mount Models: 25-742-BL (Black)

SAFE-T-ALERT

Have a safe trip!

25 Series Dual Alarms:

Double-Duty Alarm. Upgrades single 12 Volt Propane Gas alarms to a dual alarm that detects both Propane Gas and CO.

Space Saving. Compact design for RV's.

Designed for the Rugged RV Environment. Ideal for Class A Motor homes, Class B Van Campers, Class C Mini-Motor Homes, Travel Trailers, Fifth Wheels, Truck & Folding Campers.

Advanced Technology. Alarm Mute button silences alarm while RV is ventilated. Rapid recovery sensor resets when silenced or reactivates alarm if dangerous levels of Propane or CO remain.

Reliable. 12 Volt power means no missing or dead batteries to replace.

Approved. Meets RVIA/NFPA requirements.

Listed to UL 1484 RV and UL 2034 RV.



Made in USA



Replace your Propane & CO alarms that are over 5 years old!

Dual CO/Propane Alarm



25-742-TR models include trim ring that covers large existing installation cutouts.

Flush Mount Models: 25-742-WT-TR (White) 25-742-BL-TR (Black)

Have a safe trip! 25 Series Dual Alarms:

Double-Duty Alarm. Detects both gas leaks and CO gas simultaneously. Also detects Compressed Natural Gas (CNG) / Methane.

Designed for the Rugged RV Environment. Ideal for Class A Motorhomes, Class B Van Campers, Class C Mini-Motorhomes, Travel Trailers, Fifth Wheels, Truck & Folding Campers.

Advanced Technology. Alarm Mute button silences alarm while RV is ventilated. Rapid recovery sensor resets when silenced or reactivates alarm if dangerous levels of Propane or CO remain.

Low Current Draw. 1.6 Amps with solenoid valve.

Reliable. 12 Volt power means no missing or dead batteries to replace.

Approved. Meets RVIA/NFPA requirements.

Listed to UL 1484 RV and CSA 6.19.



Made in USA